No problems with core gaps, delamination and veneer overlaps common with many plywood products

Pre-conditioned boards (as mentioned in BS 8203:2017) are available upon request

Available in an easy to handle size (4'x2' & 4'x3') and in larger sheets (6, 8, 9 & 10'x4') for those BIGGER jobs

Oil tempered for extra protection against moisture ingress, and for a flatter, stronger panel

Easy to fix and lay; hard wearing with high impact resistance

Perfect as a fabricated underlay for resilient flooring as stated in BS 8203:2017

## 



## THE PROFESSIONAL'S CHOICE



A very rigid fabricated underlay for resilient floors complying with BS 8203:2017

Sub-floor preparation for carpets



Used in domestic, commercial and retail environments

Where a green and sustainable underlay is preferred

Specification	
Thickness:	4.8 & 6mm
Standard width:	1220mm*
Standard Length:	610, 915, 1220, 2440, 2745, 3050, 3660

\* Other sizes can be produced upon request, subject to volume.









## Innovation in Hardboard for Flooring Underlay

At Finnish Fibreboards we offer superior Lion<sup>™</sup> branded hardboard products which the flooring industry can depend upon. Hardboard products which meet and overcome the challenges faced by businesses as budgets are squeezed and limited resources are high on the agenda.

We have been producing hardboards since the 1930's and are extremely proud of our heritage. By using Lion <sup>™</sup> branded hardboards, you can be assured that you are using one of the best and most sustainable hardboards produced.





For more information please contact your nearest Falcon Timber Depot

T 03003 731 110 www.falcon-timber.com



Birmingham Gateshead Haydock High Wycombe Leeds Nottingham Tilbury

E birmingham@falcon-timber.com
E gateshead@falcon-timber.com
E haydock@falcon-timber.com
E highwycombe@falcon-timber.com
E leeds@falcon-timber.com
E nottingham@falcon-timber.com
E tilbury@falcon-timber.com

## CTH A Consolidated Timber Holdings Group Company