

PRODUCT FOCUS

Chipboard Loft Panels FSC®

STREloft® panels are ideal as an overlay for existing floors, or as a storage solution for use in lofts and attics. The panels have been designed with tongue and groove on the long edges, allowing the boards to slot into one another for a secure fit and easy installation. Convenient mini-panel size allows them to fit through loft hatches and ensures easy handling in tight spaces.

STREloft®

Features and Benefits

- · Easy to handle panel size
- Tongue & Groove 2 long edges for rapid and easy installation
- Convenient for DIY projects
- · Smooth furniture grade surface
- Responsibly sourced FSC® Mix 70%
- E1 emissions compliant

Panel Specifications

Thickness	18mm
Size	1220 x 253mm
Weight per board	3.6kg
Boards per pack	200

Fixing Guidance

- The long sides should be laid at 90 degrees to the joists and the ends should always meet on a joist. Floor board joints should be staggered for greater strength.
- · Fix panels in place with screws. Each screw should be countersunk and a pilot hole drilled as this makes fixing the boards easier and takes the screwheads below the level of the floor.
- · Avoid joining boards between joists as they can sag and cause a weak spot in the floor.
- · Butt joints must be positioned in the centre of joists.



FSC® Certificate Products available upon request



For more details and technical information about any of our products please get in touch with your nearest Falcon Timber Depot.

Falcon Timber

T 03003 731 110







